

Estimate for Repair and Upgradation of existing facilities of Tezpur College, Sonitpur, Tezpur,
Assam.(Buniyad bldg Indoor Stadium, and old bldg.)

Item no	Item of Works	Unit	Rate	Qty	Amount
1/13.1.1	(a) Removing white or colour wash by steel wire brushing and/ or scraping, sand papering and preparing the wall surface smooth including necessary repairs to scratches complete.	sq.m			
2/13.2.1	a) Colour washing with lime on wall surface (two coats) over and including a priming coat of white washing to give an even shade after thoroughly brooming the surface to remove all dirt, dust, mortar drops and other foreign matter.	sq.m			
	b) Extra over item no. (a) above for every subsequent coat of colour wash with lime on wall surfaces.	sq.m			
3/13.6.6	Painting one coat (excluding priming coat) on old wood and wood based surfaces with enamel paint to give an even shade including cleaning the surface of all dirt, dust and other foreign matter sand papering and stopping.				
	(i).Surfaces over 100mm in width or girth.				
	b). High gloss (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).	sq.m			
6/13.7.5	Painting one coat (excluding priming coat) on previously painted steel and other metal surface with enamel paint of approved brand and manufacture(Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac) to give an even shade including cleaning the surface of all dirt, dust and other foreign matter				
	(i).Surfaces over 100mm in width or girth.				
	b). High gloss (Asian paint/ Berger paint/ ICI paint/ J & N paint/ Nerolac).	sq.m			
7/13.8.3	Painting one coats on old G.C.I sheets with ready mixed anticorrosive paint of approved brand and shade suitable for painting over G.C.I sheets to give an even shade including the cleaning the rust patches with emery paper, dust ,dirt, grease and other foreign matter with water complete.	sq.m			
8/13.8.4	Extra over item no.13.8.3 for every subsequent coat of paint.	sq.m			
10/19.2	Providing plinth protection with bricks flat laid in cement mortar 1: 4 and finished with 15mm thick cement plaster in prop. 1:2 with a floating coat of neat cement finish.	sq.m			

11/19.4	Providing drain with cement concrete (1:3:6) 10cm thick sides 10cm thick bed over brick flat soling including 15mm thick cement plastering in prop. 1:3 finished with a floating coat of cement slurry as directed with necessary shuttering for sides and earth work in excavation of foundation trenches and refilling the sides after completion of work etc. as specified.	sq.m			